



GreenShield Inquiry Form

sales@basetek.com or 877-712-BASE (2273)



Company Quote to: _____

Project Reference _____

Contact _____

Equipment/Tag # _____

E-Mail _____

Phone _____

EQUIPMENT INFORMATION **SECTION 1**

Pump Model/Size _____

Motor Frame _____

Distance Between Shafts _____

Coupling Guard **** if inserts are required**
indicate quantity and size _____

Drawing provided _____

Other _____

Other _____

OVERALL DIMENSIONS **SECTION 2**

Length _____

Width _____

Height ** _____

**** As measured from bottom of GreenShield to bottom of limiting equipment mounting surface. DO NOT include grout allowance. Check all corners for tightest obstruction. GreenShield carries a tolerance of +/- 0.125"**

Mounting Options (choose one) **SECTION 3**

Grouted

Surface Mount (anchored with PoxyCove)

Free Float

Bury/Below Grade

Construction

Solid

Hollow Core

Have BaseTek recommend (cost/weight)

Drip Pan

Yes

No

Equipment Mounting Holes **SECTION 4**

(choose one)

303SS (standard)

316SS

C276

Titanium

Alloy 20

Material Spec (choose one)

Zanite Plus

Red Novolac

Other

Mounting Block Options **SECTION 5**

Standard Uniblock

Standard block kit (4 blocks)

Custom Risers

Transverse Uniblock (TUB)

Grout Kit Installation Kit **SECTION 6**

Yes Yes

No No

(enter inches)
Maximum epoxy grout depth

Motor Adjusters Options **SECTION 7**

BiD Adjusters

UBAK (Uniblock/TUB only - 2.875 min.)

PMA (Post-Motor Adjusters)

Notes: _____
